

PRODUCT SPECIFICATION SHEET

SPINPRO 19" Responders Oil Containment Boom. Widely used by contract emergency response companies in Ports, Marinas, Bays, Harbors and just about any inland body of water.

Specifications:	SPINPRO 19" Standard Responders Oil Containment Boom
Overall Height:	19" (48 cm),
Freeboard:	7" (17.7 cm), 6inch float, 1inch cable gain
Skirt / Draft:	12" (30.5 cm)
Fabric:	Premium 22 oz. / yd ² PVC Yellow Fabric,
Top Tension Member:	5/16" (8 mm) Galvanized Cable sheathed with a 1/2" poly tube. SS available
Ballast / Bottom Tension:	5/16" (8 mm) Hot Dip Galvanized Ballast Chain
Connectors:	ASTM Universal Marine grade aluminum connectors with stainless steel toggle pin,
Total Tensile Resistance:	17,400 lbs. (7,892 kg)
Section Length:	Available in 100' (30m) and 50' (15m).

In Compliance with:



Accessories that may be required for your spill:



Anchor Systems - In Water
Anchor Systems - On Land
Floating Marker Lights

Piling Attachment System
Boom Separators
Floating Tow Bridle

Alternative Option: If you are limited by storage space, manpower and or simply want to be able to deploy a lot faster, our 16" FAST DEPLOYMENT (Fence Boom) Oil Containment Boom along with a manual or hydraulic reel will work great for your application.

